



PIREQ 77

square, downlight, matt white, 6W, 38°, 3000K, incl. driver, clip spring

The simplicity and effectiveness of the innovative PIREQ 68 is captivating. It is available in matt black, white, or brushed aluminium, and in round or square form. Equipped with one powerful, warm white premium COB LED, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. Furthermore, it is adjustable by 38°. The electrical connection is made directly to the 230V mains supply. This luminaire contains built-in LED lamps.

TECHNICAL DATA

Item no.:	1000248
Lamps included	0
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	350 mA/V
Vertical tilting range	30 °
Length	9.0 cm
Width	9.0 cm
Height	3.5 cm
Installation diameter	7.7 cm
Installation depth	4.0 cm
Net weight	0.266 kg
Gross weight	0.32 kg
IP Code	IP 20
Safety class	II
Assembly	Recessed
Assembly details	Ceiling
Wattage	8.0 W
Lumen	700 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	white
CRI	>80



Binning	3
LXXBXX data	70/50
Service life	40000 h

Notes
