



## PIREQ 68 INTEGRATED

round, brushed aluminium, 6.5W, 38°, 3000K

The simplicity and effectiveness of the innovative PIREQ 68 INTEGRATED is captivating. It is available in matt black, white, or brushed aluminium, and in round or square form, single-headed. Equipped with a powerful, warm white premium COB LED in a tilting mount and the connection box included in the scope of supply, the downlight can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.

### TECHNICAL DATA

Item no.:	1000305
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Vertical tilting range	0 °
Vertical tilting range	30 °
Height	6.0 cm
Diameter	8.2 cm
Installation diameter	6.8 cm
Installation depth	5.7 cm
Net weight	0.186 kg
Gross weight	0.245 kg
IP Code	IP 23
Safety class	II
Impact resistance class	IK02
Impact resistance	0,200000000000000001 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	6.6 W
Lumen	580 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	aluminium



CRI	>80
Binning	6
LXXBXX data	70/50
Service life	30000 h
Ambient temperature	25 °C

**Notes**

---

---

---

---

---