



DELF C 100 PRO

light bar, 24V, 6 LED, 3000K

A rigid 24V DC LED RGB profile made from anodized aluminium and plastic. We included a connection lead, a flexible connector and mounting clips. Through the built-in plug-contacts these profiles can be connected directly to each other. The power-input to these profiles, available in several lengths, is made via a separately available 24V direct current power supply. This luminaire contains built-in LED lamps.

TECHNICAL DATA

| | |
|-------------------------|-------------|
| Item no.: | 631432 |
| Lamps included | 0 |
| Primary nominal voltage | 24V mA/V |
| Nominal voltage | 24V DC V |
| Length | 10.4 cm |
| Width | 2.0 cm |
| Height | 1.5 cm |
| Net weight | 0.03 kg |
| Gross weight | 0.043 kg |
| IP Code | IP 20 |
| Safety class | III |
| Safety class | III |
| Assembly | Surface |
| Wattage | 1.2 W |
| Lumen | 80 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 120 ° |
| Color | aluminium |
| CRI | >80 |
| Binning | 6 |
| Binning | 6 |
| LXXBXX data | 70/50 |

Accessories

| | |
|--------|---|
| 470502 | LED POWER SUPPLY , 12W, 24V |
| 631470 | FEED-IN CABLE , for DELF C PRO light bar single-colour, max. 50W, 1.5m |
| 631471 | FLEXIBLE CONNECTOR , for DELF C PRO light bar single-colour, max. 50W, 12cm |
| 631472 | MOUNTING CLIPS , for DELF C PRO light bar, 10 pieces |
| 631475 | MOUNTING CLIPS , for DELF C PRO light bar, 10 pieces, 45° |

| | |
|---------------------|---------|
| Service life | 20000 h |
| Service life | 20000 h |
| Ambient temperature | 40 °C |

Notes
